



# ToxiRAE Pro LEL

## Personal Wireless Monitor for Combustible Gases and Vapors

The ToxiRAE Pro LEL is the world's first personal wireless combustible gas monitor. The ToxiRAE Pro LEL provides safety professionals with wireless remote access to real-time instrument readings and alarm status for better visibility and faster incident response<sup>1</sup>. The ToxiRAE Pro LEL quickly detects and accurately monitors combustibles in concentrations from 0 to 100% of the lower explosive limit (LEL). With the most extensive onboard gas library in its class, the ToxiRAE Pro LEL can be programmed to automatically read in %LEL of the specified compound.

- Wireless elevates safety to the next level
- Man Down Alarm with real-time remote wireless notification
- Easy to maintain with replaceable sensor, filter, and Li-ion battery
- Fully-automatic bump testing and calibration with AutoRAE 2<sup>2</sup>

### Applications

- Construction
- Foundries
- Oil and gas
- Pharmaceutical
- Steel mills
- Utilities
- Water and wastewater
- Welding / hot work

### Optional Accessories

- AutoRAE 2 Automatic Test and Calibration System
- Multi-unit charging station for up to five monitors





### ToxiRAE Pro LEL Single -Pack Comes With:

- ToxiRAE Pro LEL monitor with sensor, alligator clip, protective rubber boot, and rechargeable battery installed
- Charging and PC communication cradle
- PC communication cable
- AC adapter (100 to 240 V, 50/60 Hz AC to 12 V DC)
- Calibration adapters
- Quick Start Guide
- CD with documentation
- Calibration card, quality certificate, and warranty/registration card

## FEATURES & BENEFITS

- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions
- 55 built-in LEL correction factors
- Largest display in its class
- Reliable, rugged, and intrinsically safe
- Continuous datalogging
- Easy to use
- Device Management with Honeywell SafetySuite

# ToxiRAE Pro LEL Specifications

| SPECIFICATIONS <sup>4</sup>         |   |
|-------------------------------------|---|
| SIZE                                | 4.6" H x 2.4" W x 1.2"D (118 x 60 x 30 mm)  |
| WEIGHT                              | 8.29 oz. (235 g.)   |
| SENSOR                              | Catalytic bead LEL sensor with 0 to 100% LEL range and 1% LEL resolution. Response time (T90) < 15 seconds  |
| DETECTABLE GASES                    | Combustible gases and vapors from paints, coatings, fuels, degreasers, adhesives, solvents, resins, etchers, inks, pesticides, herbicides, etc. using 5.5 onboard correction factors  |
| BATTERY                             | Rechargeable Li-ion battery<br>- Operating time: > 12 hours (normal operation, non-wireless)<br>- Recharge time: < 4 hours through charging cradle  |
| DISPLAY                             | Graphical LCD display with white LED backlighting (activated when monitor is in alarm or with a button press)   |
| DISPLAY READOUT                     | - Real-time reading of % of lower explosive limit (LEL); battery status; data logging on/off; wireless on/off and reception quality<br>- Peak values  |
| KEYPAD                              | 2 buttons for operation and programming   |
| SAMPLING                            | Diffusion   |
| CALIBRATION                         | Automatic with AutoRAE 2 Test and Calibration System <sup>2</sup> or manual   |
| ALARM MODES                         | - Wireless remote alarm notification <sup>1</sup> ; audible (95 dB @ 30 cm), vibration, visible alarm (ashing bright red LEDs), and on-screen indication of alarm conditions<br>- Man Down Alarm with pre-alarm and real-time remote wireless notification  |
| DATALOGGING                         | - Continuous datalogging <sup>3</sup> with a three-month capacity (at one-minute intervals)<br>- User-configurable datalogging interval (from 1 to 3,600 seconds)   |
| COMMUNICATION AND DATA DOWNLOAD     | - Data download and instrument set-up on PC via charging and PC comm. cradle<br>- Data download via AutoRAE 2 Automatic Test and Calibration System <sup>2</sup><br>- Wireless data and status transmission via built-in RF modem (optional)  |
| WIRELESS NETWORK                    | ProRAE Guardian Real-Time Wireless Safety System or Closed-Loop Network with the EchoView Host  |
| WIRELESS FREQUENCY                  | ISM license-free bands  |
| WIRELESS RANGE (TYPICAL)            | ToxiRAE Pro PID to Mesh Router, EchoView Host, or Mesh Reader <sup>2</sup> ~ 330 feet (100 meters)<br>ToxiRAE Pro PID to RAElink3 Mesh or RAElink3 Z1 Mesh modems ~ 33 feet (10 meters)   |
| OPERATING TEMPERATURE               | -4° to 131°F (-20° to 55°C)   |
| HUMIDITY                            | 0% to 95% relative humidity (non-condensing)  |
| HAZARDOUS LOCATION APPROVALS        | CSA:  Class I, Division 1, Groups A, B, C and D. T-code T4 Class I, Zone 0 A/Exia IIC T4<br>ATEX:  II 1G, Ex ia IIC Ga T4<br>IECEX: Ex ia IIC Ga T4<br>China Ex: Ex ia IIC T4 |
| CE COMPLIANCE (EUROPEAN CONFORMITY) | EMC directive: 2004/108/EC. R&TTE directive: 1999/5/EC. ATEX directive: 94/9/EC   |
| PERFORMANCE TEST COMPLIANCE         | C22.2 No 152<br>ANSI/ISA-12.13.01   |
| WARRANTY                            | - Two years on non-consumable components<br>- One year on sensor, fan, battery, and other consumable parts  |

## ORDERING INFORMATION (MODEL: PGM-1820)

- Wireless or non-wireless versions are available<sup>1</sup>
- Bulk packages of 10 units are available
- Refer to the Portables Pricing Guide for part numbers for monitors, accessories, maintenance kits, gas, sensors, and replacement parts



- 1 Wireless units have a functioning RF modem and are ready for wireless deployments; non-wireless units cannot be upgraded to wireless. Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.
- 2 Contact RAE Systems for availability.
- 3 Available with Industrial Hygiene configurations only.
- 4 Specifications are subject to change.

## For more information

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)  
[www.raesystems.com](http://www.raesystems.com)

### Europe, Middle East, Africa

Life Safety Distribution GmbH  
Tel: 00800 333 222 44 (Freephone number)  
Tel: +41 44 943 4380 (Alternative number)  
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)  
[gasdetection@honeywell.com](mailto:gasdetection@honeywell.com)

### Americas

Honeywell Analytics Distribution Inc.  
Tel: +1 847 955 8200  
Toll free: +1 800 538 0363  
[detectgas@honeywell.com](mailto:detectgas@honeywell.com)  
Honeywell RAE Systems  
Phone: +1 408 952 8200  
Toll Free: +1 888 723 4800

### Asia Pacific

Honeywell Analytics Asia Pacific  
Tel: +82 (0) 2 6909 0300  
India Tel: +91 124 4752700  
China Tel: +86 10 5885 8788-3000  
[analytics.ap@honeywell.com](mailto:analytics.ap@honeywell.com)

### Technical Services

EMEA: [HAexpert@honeywell.com](mailto:HAexpert@honeywell.com)  
US: [ha.us.service@honeywell.com](mailto:ha.us.service@honeywell.com)  
AP: [ha.ap.service@honeywell.com](mailto:ha.ap.service@honeywell.com)

Datasheet\_ToxiRAE Pro LEL\_DS-1065-07\_EMEA-EN  
05/18 ©2018 Honeywell International Inc.

Device Management with  
Honeywell SafetySuite



[honeywellanalytics.com/SafetySuite](http://honeywellanalytics.com/SafetySuite)

**Honeywell**